


Flying Probe G90 XXL



- Premium double sided Flying Probe system
- Multi Image Testing
- Testing voltage up to 1000 Volt
- HiPot measurement (1000V)
- Micro Short Detection
- Embedded resistor test
- Embedded capacitor test
- **Max test size 63" x 47.2" / 1600mm x 1200mm**
- High speed lead screw driven motion system mounted on a marble frame
- Glass scale system
- Front and rear fully automatic camera alignment
- Electrical stretch frame – no compressed air connection required
- Quick frame for fast set up of rigid boards
- User friendly, high-speed software made specifically by Gardien
- Plug and Play link with the Gardien AC8
- CE Certificated

PLEASE CONTACT US FOR MORE INFORMATION:

Canada
info.ca@gardien.com
 +1 (416) 292 0726

China
Info.cn@gardien.com
 +86 512 5770 7951

Germany
Info.ge@gardien.com
 +49 6431 929730

Japan
info.jp@gardien.com
 +81 3 3904 6230

Taiwan
Info.tw@gardien.com
 +886 3355 1668

USA
Info.us@gardien.com
 +1 (503) 430 8980

Group
Info.group@gardien.com
 +65 6593 6380

G90 XXL Specification

MECHANICS

No. of test probes	4 (2 front / 2 back) High Speed Z-Axis with soft touch (requires soft touch probes)	
Test probe pressure	2-10 g	
No. of CCD-cameras	2 (1front/1back)- Fully automatic camera alignment for easy and fast compensation of board registration	
Max test area (x/y)	63"x 47.2"	1600mm x 1200mm
Min board size (x/y)	4" x 4"	100mm x 100mm
Max board thickness	320 mil	8mm
Min board thickness (standard)	5mil	0.12mm
Repeatable accuracy +/-	0.3 mil	7.5µm
Resolution (x/y) +/-	0.3 mil	7.5µm
Smallest testable pad size	2mill	50µm
Smallest testable distance/pitch	3mil	75µm
Board Loading option	Stretch/Quick Frame	

DIMENSIONS & ENVIRONMENTAL CONDITIONS

Width	117.3"	2980mm
Depth	39"	992 mm
Height	74,5"	1893mm (without light)
	83.5"	2122m (with light)
Weight	5070lbs	2300kg
Air humidity	45-65% not condensing	
Room Temp.	64° -90°F	18°-32°C
Power supply	400V, 50/60Hz, 1000W 3 Phase	

ELECTRONICS

Test voltage	20V up to 1000V (adjustable)
Test current	5mA up to 500mA (adjustable)
Continuity test	1 Ω up to 5000 Ω (dependent on the current, smaller current = larger resistance)
Isolation test	1 M Ω up to 500 M Ω

OPTIONS

Hardware

- > Vacuum plate: Single Sided for Flex / Thin core/ Inner layer (min Board thickness 3mil/80µm)
- > Multi Board (Quick frame)

Software

- > Data preparation software (Certified Ucamco)
- > Verification software (Certified Ucamco)
- > Test floor integration (TFI) capability

SOFTWARE

Operating Software	Windows 10 (English Version)
User Interface	Gardien FPX with multi Language support (Chinese, Japanese, Spanish,)
Data Input formats	MNF1, MNF2, IPC 356A/B, EMMA
Test Floor Integration	IT based communication and data exchange between Universal Grid, Flying Probe and Verification SW