

KAIMA GUQAA 1.7"



- Electrical Tester Universal Grid System
- Quad Density
- High Reliability
- Extreme Flexibility
- High Modularity
- Solid mechanical Structure
- Remarkable Throughput
- 1.7 inch fixture
- Top to Bottom head alignment
- Sorted GOOD and BAD stack
- Compatible with all Universal Grid tester formats

PLEASE CONTACT US FOR MORE INFORMATION:

Canada
info.ca@gardien.com
 +1 (416) 292 0726

China
Info.cn@gardien.com
 +86 512 5770 7951

Germany
Info.ge@gardien.com
 +49 6431 929730

Japan
info.jp@gardien.com
 +81 3 3904 6230

Taiwan
Info.tw@gardien.com
 +886 3355 1668

USA
Info.us@gardien.com
 +1 (503) 430 8980

Group
Info.group@gardien.com
 +65 6593 6380

GUQAA 1.7" Specification

TEST SYSTEM

Operating Interface Language	English, Chinese	
Grid Density	50 mil (QD)	
Test points	81920 per side (163840)	
Electronic Test Speed	4096 - 8192 TP/s	
Max test area (x/y)	16,0" x 12,8"	406 mm x 325 mm
Min test size (x/y)	2" x 2"	50 mm x 50 mm
Test Board Size max.	16" x 12,8"	406 mm x 325 mm
Test Board Thickness Automatic Mode	0,6 mm – 5,0 mm	
Test Board Thickness Manual Mode	0,2 mm – 10,0 mm	
Defect Sorting	Automatic Mode: Good / Bad Stacker	
Fixture Spec	1.7" 43mm height, smallest test pin 0,15 mm	
Net List Format	KM_SEU Format, or L&M test format	
Defect Confirmation	Repair Software	

ELECTRONICS

Test voltage	50V – 300V	BR Test Option
Test current	20 mA (max.)	
Continuity Test	10 Ω – 1000 Ω	
Isolation Test	1 MΩ – 100 MΩ	
Power supply	380 V, 3-phase, 4Wire (5KW)	

OPTIONS

DIMENSIONS & ENVIRONMENTAL CONDITIONS

Width	136,61 "	3470 mm
Depth	46,85 "	1190 mm
Height	68,5 "	1740 mm
Weight	5621,78 lbs	2550 kg
Air pressure	5,8 – 7,8 bar dry and oil free	
Air humidity	50 - 65% - not condensing	
Room temperature	68° - 77 °F	20 - 25 °C

INCLUDED IN SHIPMENT

Repair Software
